



Product certificate K12221/10

Issued 2021-03-15

Replaces K12221/09

Page 1 of 3

Water meters

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Zenner International GmbH & Co . KG

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline

BRL-K618: "Water meters" dated 2018-01-15 and **BRL-K618 [A1]** dated 2020-07-07

which covers the requirements of

EN-ISO 4064-1: 2017: "Water meters for cold potable water and hot water - Part 1: Metrological and technical requirements".

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273
P.O.Box 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
info@kiwa.nl
www.kiwa.nl

Company

Zenner International GmbH & Co . KG
Römerstadt 6
66121 SAARBRÜCKEN
Germany
Tel. +49 (0)681 996 76-0
info@zenner.de
www.zenner.com

Representative

Raminex International B.V.
Landzigt 34
3454 PE UTRECHT
The Netherlands
Tel. +31 30 241 1224
info@raminex.nl
www.raminex.nl



Certification process
consists of initial and
regular assessment of:

- quality system
- product

Water meters

PRODUCT SPECIFICATION

The products mentioned below belong to this technical approval-with-product certificate

Velocity meters, MNK, MAT50, MAP16

Permanent volume flow $Q_3 = 2,5 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 200$

Permanent volume flow $Q_3 = 4 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 200$

Permanent volume flow $Q_3 = 6,3 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 200$

Permanent volume flow $Q_3 = 10 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 200$

Permanent volume flow $Q_3 = 16 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 200$

Volume meters, RTKD MAT50, MAP16

Permanent volume flow $Q_3 = 1,6 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 250$

Permanent volume flow $Q_3 = 2,5 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 400$

Permanent volume flow $Q_3 = 4 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 400$

Permanent volume flow $Q_3 = 6,3 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 200$

Permanent volume flow $Q_3 = 10 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 315$

Volume meters, RTKD-L MAT50, MAP16

Permanent volume flow $Q_3 = 1,6 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 250$

Permanent volume flow $Q_3 = 2,5 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 400$

Permanent volume flow $Q_3 = 4 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 400$

Permanent volume flow $Q_3 = 6,3 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 200$

Permanent volume flow $Q_3 = 10 \text{ m}^3/\text{h}$, $R (Q_3/Q_1) \leq 315$

Fitness for contact with drinking water

This product is approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).

These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

MARKING

The Kiwa®-mark products are marked with the word mark "KIWA 

Place of the mark: on the outside of the water meter

Compulsory specifications:

- Unit of measurement: (m^3);
- Numerical value of Q_3 ;
- Ratio Q_3/Q_1 , preceded by "R", i.e. "R160";
- Ratio Q_2/Q_1 , (where it differs from 1,6);
- MAP (where it differs from 1 MPa (10 bar));
- Direction of flow by an arrow
- The letter V or H, if the meter can only be operated in the vertical or horizontal position;
- MAT, (where it differs from T30);
- Pressure loss class (where it differs from $\Delta P 63$);
- Classes on sensitivity to irregularities in velocity field;
- The name or trademark of the manufacturer;
- Year of manufacture, last 2 digits
- Serial number, as near as possible to the indicating device;
- The pattern approval sign according to European regulations;
- Climatic and mechanical environment: severity level;
- EMC Class;
- Output signals for ancillary devices: type/levels if any;

Water meters

- External power supply requirements: voltage – frequency.

Method of marking:

- Non-erasable;
- visible after assembly.

APPLICATION AND USE

The products are intended to be used in closed and filled drinking water installations in order to measure quantities of water flowing through per time and in total with a maximum water temperature of 50°C.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Zenner International GmbH & Co . KG
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.